




**Pushing Performance**  
Since 1945

## Han A Hood Angled Entry 2 Pegs M20 Bla



|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 20 003 0627                                                                        |
| Specification      | Han A Hood Angled Entry 2 Pegs M20 Bla                                                |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19200030627">https://b2b.harting.com/19200030627</a> |

### Identification

|                          |                    |
|--------------------------|--------------------|
| Category                 | Hoods/Housings     |
| Series of hoods/housings | Han A <sup>®</sup> |
| Type of hood/housing     | Hood               |

### Version

|                      |                                                     |
|----------------------|-----------------------------------------------------|
| Size                 | 3 A                                                 |
| Version              | Side entry                                          |
| Cable entry          | 1x M20                                              |
| Locking type         | Single locking lever                                |
| Field of application | Standard Hoods/housings for industrial applications |

### Technical characteristics

|                                        |                                                    |
|----------------------------------------|----------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C                                    |
| Note on the limiting temperature       | For use as a connector according to IEC 61984.     |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 / IP67 with seal screw 09 20 000 9918 |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                      |

### Material properties

|                                           |                      |
|-------------------------------------------|----------------------|
| Material (hood/housing)                   | Polycarbonate (PC)   |
| Colour (hood/housing)                     | RAL 9005 (jet black) |
| Material flammability class acc. to UL 94 | V-0                  |
| RoHS                                      | compliant            |



**Pushing Performance**  
Since 1945

## Material properties

|                                     |                      |
|-------------------------------------|----------------------|
| ELV status                          | compliant            |
| China RoHS                          | e                    |
| REACH Annex XVII substances         | Not contained        |
| REACH ANNEX XIV substances          | Not contained        |
| REACH SVHC substances               | Not contained        |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels  | R1 (HL 1-3)          |
|                                     | R7 (HL 1-3)          |

## Specifications and approvals

|           |        |
|-----------|--------|
| Approvals | DNV GL |
| CE        | Yes    |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 10                                       |
| Net weight                     | 13 g                                     |
| Country of origin              | Romania                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140124479                            |
| eCl@ss                         | 27440202 Shell for industrial connectors |