

Han 10B-HTE2-f. DL-M25-rect



Image is for illustration purposes only. Please refer to product description.

Part number	19 30 010 0466
Specification	Han 10B-HTE2-f. DL-M25-rect
HARTING eCatalogue	https://b2b.harting.com/19300100466

Identification

Category	Hoods/Housings
Series of hoods/housings	Han [®] B
Type of hood/housing	Hood
Description of hood/housing	72 mm high
Type	High construction

Version

Size	10 B
Version	Top entry
Cable entry	2x M25
Locking type	Double locking lever
Field of application	Standard hoods/housings for industrial connectors

Technical characteristics

Limiting temperature	-40 ... +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65 IP66 IP67
Type rating acc. to UL 50 / UL 50E	4 4X 12



Pushing Performance
Since 1945

Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)

Specifications and approvals

Approvals	DNV GL
CE	Yes

Commercial data

Packaging size	1
Net weight	173.4 g
Country of origin	China
European customs tariff number	85389099
GTIN	5713140164420
eCl@ss	27440202 Shell for industrial connectors